

Overview

The Huawei EchoLife HG8245H is a routing-type ONT in the Huawei all-optical access solution. It uses the GPON technology to implement ultra-broadband access for users. It provides 4 GE+2 POTS+1 USB+1 Wi-Fi(4 GE ports, 2 POTS ports, 1 USB port,and 1 2.4G WiFi port). The high forwarding performance ensures the user experience of voice, data, and HD video services, and provides customers with an ideal all-optical access solution and future-oriented service support capability.

Quick Specification

Table 1 shows the Quick Specification.

Model	EchoLife HG8245H
Dimensions (W x D x H)	176 mm x 138.5 mm x 28 mm (without an external antenna)
Weight	About 500g
Operating Temperature	0°C to +40°C
Operating Humidity	5% to 95% RH (non-condensing)
Power Adapter Input	100-240V AC, 50/60 Hz
System Power Supply	11-14V DC, 2A
Static Power Consumption	5 W
Maximum Power Consumption	15.5W

Figure 1 shows the appearance of EchoLife HG8245H.





Product Details

Interface Parameters

GPON Port	<ul style="list-style-type: none"> • Class B+ • Receiver sensitivity: -27dBm • Wavelengths: US 1310nm, DS 1490nm • WBF • Flexible mapping between GEM Port and TCONT • GPON: consistent with the SN or password authentication defined in G.984.3 • Bi-directional FEC • SR-DBA and NSR-DBA
Ethernet Port	<ul style="list-style-type: none"> • Ethernet port-based VLAN tags and tag removal • 1:1 VLAN, N:1 VLAN, or VLAN transparent transmission • QinQ VLAN • Limit on the number of learned MAC addresses • MAC address learning
POTS Port	<ul style="list-style-type: none"> • Maximum REN: 4 • G.711A/μ, G.729a/b, and G.722 encoding/decoding • T.30/T.38/G.711 fax mode • DTMF • Emergency calls (with the SIP protocol)
USB Port	<ul style="list-style-type: none"> • USB2.0 • FTP-based network storage
WLAN	<ul style="list-style-type: none"> • IEEE 802.11 b/g/n • 2 x 2 MIMO • Antenna gain: 2 dBi • WMM • Multiple SSIDs • WPS

Product Function

Smart Interconnection	<ul style="list-style-type: none"> • Smart Wi-Fi coverage (V300R015C10) • SIP/H.248 auto-negotiation • Any port any service • Parental control (V300R015C00) • L2/L3(IPv4) forwarding: 1G uplink, 2G downlink
Smart Service	<ul style="list-style-type: none"> • Smart Wi-Fi sharing: Portal/802.1x authentication (V300R015C10) • SoftGRE-based sharing (V300R015C10)





	<ul style="list-style-type: none"> • Association of one account with two POTS ports
Smart O&M	<ul style="list-style-type: none"> • IPTV video quality diagnosis (V300R015C10) • Variable-length OMCI messages • Active/Passive rogue ONT detection and isolation • Call emulation, and circuit test and loop-line test • PPPoE/DHCP simulation testing • WLAN emulation
Layer 3 Features	<ul style="list-style-type: none"> • PPPoE/Static IP/DHCP • NAT/NAPT • Port forwarding • ALG, UPnP • DDNS/DNS server/DNS client • IPv6/IPv4 dual stack, and DS-Lite • Static/Default routes • Multiple services on one WAN port
Multicast	<ul style="list-style-type: none"> • IGMP v2/v3 proxy(V300R015C00)/snooping • MLD v1/v2 snooping • Multicast services through Wi-Fi
QoS	<ul style="list-style-type: none"> • Ethernet port rate limitation • 802.1p priority • SP/WRR/SP+WRR • Broadcast packet rate limitation
Security	<ul style="list-style-type: none"> • SPI firewall • Filtering based on MAC/IP/URL addresses
Common O&M	<ul style="list-style-type: none"> • OMCI/Web UI/TR069 • Dual-system software backup and rollback
Power Saving	<ul style="list-style-type: none"> • Dynamic power saving • Indicator power saving • Scheduled Wi-Fi shutdown (V300R015C00)

Get More Information

Do you have any question about the EchoLife HG8245H?

Contact us now via info@hi-network.com.

Specification

EchoLife HG8245H Specification	
Dimensions (W x D x H)	176 mm x 138.5 mm x 28 mm (without an external antenna)
Weight	About 500g





Operating Temperature	0°C to +40°C
Operating Humidity	5% to 95% RH (non-condensing)
Power Adapter Input	100-240V AC, 50/60 Hz
System Power Supply	11-14V DC, 2A
Static Power Consumption	5 W
Maximum Power Consumption	15.5W
Ports	2POTS+4GE+Wi-Fi+USB
Indicators	POWER/PON/LOS/LAN/TEL/USB/WLAN/WPS
GPON Port	<ul style="list-style-type: none"> • Class B+ • Receiver sensitivity: -27dBm • Wavelengths: US 1310nm, DS 1490nm • WBF • Flexible mapping between GEM Port and TCONT • GPON: consistent with the SN or password authentication defined in G.984.3 • Bi-directional FEC • SR-DBA and NSR-DBA
Ethernet Port	<ul style="list-style-type: none"> • Ethernet port-based VLAN tags and tag removal • 1:1 VLAN, N:1 VLAN, or VLAN transparent transmission • QinQ VLAN • Limit on the number of learned MAC addresses • MAC address learning
POTS Port	<ul style="list-style-type: none"> • Maximum REN: 4 • G.711A/μ, G.729a/b, and G.722 encoding/decoding • T.30/T.38/G.711 fax mode • DTMF • Emergency calls (with the SIP protocol)
USB Port	<ul style="list-style-type: none"> • USB2.0 • FTP-based network storage
WLAN	<ul style="list-style-type: none"> • IEEE 802.11 b/g/n • 2 x 2 MIMO • Antenna gain: 2 dBi • WMM • Multiple SSIDs • WPS

Want to Buy

Get a Quote



[Get a Quote](#)



[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)

Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: [echo.hinetwork](https://www.skype.com/people/echo.hinetwork)

WhatsApp Business: +8618057156223

