

Overview

Cisco Aironet® 1560 Series Outdoor Access Points offer the latest 802.11ac Wave 2 functions in a rugged, low-profile housing that service providers and enterprises can deploy easily.

Ideal for applications requiring rugged outdoor Wi-Fi coverage, the Cisco Aironet 1560 Series Access Points offer the latest IEEE 802.11ac Wave 2 radio standard in a compact, aesthetically pleasing, easy-to-deploy package. The 1560 Series offers flexible deployment options for service providers and enterprise networks, that need the fastest links possible for mobile, outdoor clients (smartphones, tablets, and laptops) and wireless backhaul. With options for internal or external antennas, the 1560 Series Access Points give network operators the flexibility to balance their desired wireless coverage with their need for easy deployment.

Quick Specification

Table 1 shows the quick specs of AIR-AP1562I-M-K9.

| | |
|------------------------------------|---|
| Part Number | AIR-AP1562I-M-K9 |
| Description | 802.11ac Wave 2 Low-Profile Outdoor AP, Internal Antenna, M Regulatory Domain |
| 802.11ac Wave 1 and 2 capabilities | <ul style="list-style-type: none"> • 3 x 3 MIMO with three spatial streams • Multi- and single-user MIMO • Maximal Ratio Combining (MRC) • 802.11ac beamforming (transmit beamforming) • 20-, 40-, and 80-MHz channels • PHY data rates up to 1.3 Gbps (80 MHz in 5 GHz) • Packet aggregation: A-MPDU (Tx/Rx) and A-MSDU (Tx/Rx) • 802.11 Dynamic Frequency Selection (DFS) • Cyclic-Shift-Diversity (CSD) support |
| Regulatory Domain | M (M regulatory domain): <ul style="list-style-type: none"> • 2.412 to 2.472 GHz, 13 channels • 5.500 to 5.580 GHz, 5 channels • 5.660 to 5.700 GHz, 3 channels • 5.745 to 5.805 GHz, 4 channels |
| Antenna | Internal Antenna |
| Interfaces | <ul style="list-style-type: none"> • WAN port 10/100/1000BASE-T Ethernet, autosensing (RJ-45), PoE in • SFP port (fiber or electrical) • Management console port (RJ-45) • Multicolor LED • DC power input • Reset button |
| Dimensions (W x L x H) | 9.0 x 6.8 x 3.9 in. (22.9 x 17.1 x 9.8 cm) |
| Weight | 5.6 lb (2.5 kg) |

Figure 1 shows the appearance of AIR-AP1562I-M-K9.



Get More Information

Do you have any question about the AIR-AP1562I-M-K9?

Contact us now via info@hi-network.com.

Specification

| AIR-AP1562I-M-K9 Specification | |
|------------------------------------|--|
| Description | 802.11ac Wave 2 Low-Profile Outdoor AP, Internal Antenna, M Regulatory Domain |
| Regulatory Domain | M (M regulatory domain): <ul style="list-style-type: none"> • 2.412 to 2.472 GHz, 13 channels • 5.500 to 5.580 GHz, 5 channels • 5.660 to 5.700 GHz, 3 channels • 5.745 to 5.805 GHz, 4 channels |
| 802.11n (and related) capabilities | <ul style="list-style-type: none"> • 3 x 3 MIMO with three spatial streams • MRC • 20- and 40-MHz channels • PHY data rates up to 450 Mbps |

AIR-AP1562I-M-K9 Datasheet

Get a Quote



HI-NETWORK.com
Your Global Original Network Supplier

| | |
|------------------------------------|---|
| | <ul style="list-style-type: none"> • Packet aggregation: A-MPDU (Tx/Rx) and A-MSDU (Tx/Rx) • 802.11 DFS • CSD support |
| 802.11ac Wave 1 and 2 capabilities | <ul style="list-style-type: none"> • 3 x 3 MIMO with three spatial streams • Multi- and single-user MIMO • Maximal Ratio Combining (MRC) • 802.11ac beamforming (transmit beamforming) • 20-, 40-, and 80-MHz channels • PHY data rates up to 1.3 Gbps (80 MHz in 5 GHz) • Packet aggregation: A-MPDU (Tx/Rx) and A-MSDU (Tx/Rx) • 802.11 Dynamic Frequency Selection (DFS) • Cyclic-Shift-Diversity (CSD) support |
| Antenna type | Internal Antenna |
| Maximum conducted transmit power | <ul style="list-style-type: none"> • 2.4 GHz: 29 dBm with 3 antennas • 5 GHz: 29 dBm with 3 antennas |
| Interfaces | <ul style="list-style-type: none"> • WAN port 10/100/1000BASE-T Ethernet, autosensing (RJ-45), PoE in • SFP port (fiber or electrical) • Management console port (RJ-45) • Multicolor LED • DC power input • Reset button |
| Uplink options | Ethernet, SFP, and wireless mesh |
| Dimensions (W x L x H) | 9.0 x 6.8 x 3.9 in. (22.9 x 17.1 x 9.8 cm) |
| Weight | 5.6 lb (2.5 kg) |
| Environmental | <p>Operating temperature:</p> <ul style="list-style-type: none"> • -40 to 65°C (-40 to 149°F) ambient air with no solar loading • -40 to 55°C (-40 to 131°F) ambient air with solar loading <p>Storage temperature: -40 to 85°C (-40 to 185°F)</p> <p>Humidity: 5 - 95%, non-condensing</p> <p>Wind resistance:</p> <ul style="list-style-type: none"> • Up to 100-mph sustained winds • Up to 165-mph wind gusts |
| Power consumption | 32 W (3x3:3, full power) |
| Powering options | <ul style="list-style-type: none"> • AC (with AIR-PWRADPT-RGD1=, AC/DC outdoor power adapter) • 44-57 VDC input • Universal Power of Ethernet (Cisco UPoE+ and Cisco UPoE), 802.3at • Cisco power injectors: AIR-PWRINJ-60RGD1= (outdoor rated, 60W, with NEMA 5-15 AC plug) AIR-PWRINJ-60RGD2= (outdoor rated, 60W, unterminated AC cable) AIR-PWRINJ6= (indoor, 802.3at) <p>Note: If 802.3at Power over Ethernet (PoE) is the source of power, the 1562I radios will shift from 3 x 3 to 2 x 2.</p> |
| Warranty | 1-year limited hardware warranty |





Want to Buy

[Get a Quote](#)

[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)

Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: [echo.hinetwork](https://www.skype.com/people/echo.hinetwork)

WhatsApp Business: +8618057156223

