

[Get a Quote](#)

Overview

Cisco ASA with Firepower Services brings distinctive threat-focused next-generation security services to the Cisco ASA 5500-X Series Next-Generation Firewalls and Cisco ASA 5585-X Adaptive Security Appliance firewall products. It provides comprehensive protection from known and advanced threats, including protection against targeted and persistent malware attacks. Cisco ASA is the world's most widely deployed, enterprise-class stateful firewall.

Quick Specification

Table 1 shows the Quick Specification.

Product Name	ASA5506-SEC-BUN-K9
Product Description	ASA 5506-X with Firepower Services Security Appliance 8-Ports GigE with Security Plus
Product Line	ASA
Product Series	5500-X
Product Model	5506-X
Product Type	Network Security/Firewall Appliance
Technical Information	
Encryption Standard	AES 3DES
Interfaces/Ports	
Total Number of Ports	8
USB	Yes
PoE (RJ-45) Port	No
Number of Network (RJ-45) Ports	8
Network & Communication	
Ethernet Technology	Gigabit Ethernet
Network Standard	10/100/1000Base-T
Management & Protocols	
Manageable	Yes
Wireless Specifications	
Wireless LAN	No
Physical Characteristics	
Form Factor	Desktop Rack-mountable

Height	1.7"
Width	8.9"
Depth	7.9"
Other Information	
Product Family	ASA 5500-X
Broadband Transmission Speed	100 Mbit/s

Figure 1 shows the appearance of ASA5506-SEC-BUN-K9.



Get More Information

Do you have any question about the Cisco ASA5506-SEC-BUN-K9?

Contact us now via info@hi-network.com.

Specification

Cisco ASA 5506-X With Firepower Services	
Maximum application control (AVC) throughput	250 Mbps
Maximum application control (AVC) and NGIPS throughput	125 Mbps
Maximum concurrent sessions	50000
Maximum New Connections per second	5000
Application control (AVC) or IPS sizing throughput [440 byte HTTP]	90 Mbps
Supported applications	More than 3,000
URL categories	80+
Number of URLs categorized	More than 280 million
Centralized configuration, logging, monitoring, and reporting	Multi-device Cisco Security Manager (CSM) and Cisco FireSIGHT Management Center

On-Device Management	ASDM 7.3.x
Stateful inspection throughput	750 Mbps
Stateful inspection throughput	300 Mbps 100 Mbps
Users/nodes	Unlimited
IPsec VPN peers	50
Cisco Cloud Web Security users	275
Cisco AnyConnect Premium/Apex VPN peers	2; 50
Concurrent connections	50000
New connections per second	5000
VLANs	Without Security Plus: With Security Plus: 5; 30
High availability	Active/Standby
Expansion slot	N/A
USB 2.0 ports	1
Integrated I/O	8 x 1GE
Dedicated management port	Yes (1 GE)
Memory	4 GB
Solid-state drive	64 GB mSata

Want to Buy

Get a Quote



[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)

Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: echo.hinetwork

WhatsApp Business: +8618057156223

