

Overview

The Cisco C1300-24FP-4G is a versatile and robust networking solution designed for efficient power and high-speed connectivity. Featuring 24x 10/100/1000 PoE+ ports with a 370W power budget and 4x Gigabit SFP uplink ports, this switch enables seamless integration with a variety of network devices. Ideal for growing businesses or enterprise environments, the Cisco C1300-24FP-4G delivers reliable performance and scalability.

Quick Specification

Table 1 shows the quick specification.

Model	C1300-24FP-4G
Dimension	444.3 x 350 x 43.94 mm (17.49 x 13.77 x 1.73 in)
Weight	4.6 kg (10.14 lb)
Operating Temperature	23° to 122°F (-5° to 50°C)
Operating Humidity	10% to 90%, relative, noncondensing
Ports	24x 10/100/1000 PoE+ ports with 370W power budget
Combo Ports	4x Gigabit SFP
Form Factor	Fixed Configuration

Figure 1 shows the appearance of C1300-24FP-4G.





Product Details

Product Features

- Provides 24 high-speed PoE+ ports for power-hungry devices.
- 370W power budget suitable for IP cameras, VoIP phones, and access points.
- 4x Gigabit SFP uplink ports for flexible network expansion.
- Layer 2 switching capabilities for efficient network management.
- Energy-efficient design with advanced power-saving features.

Product Applications

- Small to medium-sized enterprise offices needing reliable network connectivity and PoE support.
- Large campus environments requiring scalable network infrastructure.
- Retail stores and service providers needing high-performance data and power transmission.

Supported Options

Accessory	Model
Cisco Stackwise Cable	STACK-T1-50CM
SFP Transceiver Modules	GLC-SX-MMD
Power Supply Module	PWR-C1-715WAC-P

Compare to Similar Items

Model	Differences
Cisco C1200-24P-4X	Provides 4x 10G SFP+ uplink ports
Cisco C1000-24FP-4G-L	16x PoE+ ports with lower power budget
Cisco C2960X-24PD-L	8x PoE+ ports, higher overall data throughput capacity

Get More Information

Do you have any questions about the C1300-24FP-4G?

Contact us now via info@hi-network.com.





Specification

C1300-24FP-4G Datasheet	
Ports	24x 10/100/1000 PoE+ ports with 370W power budget
Combo Ports	4x Gigabit SFP
Mounting	Rack-mountable
Forwarding Rate	41.66 Mpps
Switching Capacity	56.0 Gbps
Power	100-240V 50-60 Hz, internal, universal
PoE	Supported
Dimension	444.3 x 350 x 43.94 mm (17.49 x 13.77 x 1.73 in)
Weight	4.6 kg (10.14 lb)
Operating Temperature	23° to 122°F (-5° to 50°C)
Operating Humidity	10% to 90%, relative, noncondensing
Console port	Cisco standard RJ-45 console port and USB Type C port
USB port	USB Type C port on the front panel of the switch for easy file and image management as well as console port
Buttons	Reset button
Cabling type	Unshielded Twisted Pair (UTP) Category 5e or better for 1000BASE-T
LEDs	System, Link/Act, PoE, Speed
Flash	512 MB
CPU	ARM dual-core at 1.4 GHz
DRAM	1 GB DDR4
Certifications	UL (UL 62368), CSA (CSA 22.2), CE mark, FCC Part 15 (CFR 47) Class A

Want to Buy

Get a Quote

[Learn More](#) about Hi-Network[Search](#) our Resource Library[Follow](#) us on LinkedInContact for [Sales or Support](#)



Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: [echo.hinetwork](https://www.skype.com/people/echo.hinetwork)

WhatsApp Business: +8618057156223

