

Overview

Introducing the Cisco C1300-24T-4X, a powerful and versatile switch designed to meet the growing demands of modern network infrastructures. With 24x 10/100/1000 ports and 4x 10 Gigabit SFP+ ports, this switch offers robust connectivity and exceptional performance, making it ideal for both small and medium-sized businesses.

Quick Specification

Table 1 shows the quick specification.

Model	C1300-24T-4X
Dimension	445 x 240 x 44 mm (17.5 x 9.45 x 1.73 in)
Weight	3.14 kg (6.92 lb)
Operating Temperature	23° to 122°F (-5° to 50°C)
Operating Humidity	10% to 90%, relative, noncondensing
Ports	24x 10/100/1000 ports
Combo Ports	4x 10 Gigabit SFP+
Form Factor	Fixed Configuration

Figure 1 shows the appearance of C1300-24T-4X.



Product Details

Product Features

- High-density port configuration with 24x 10/100/1000 ports
- 4x 10 Gigabit SFP+ uplink ports for high-speed connectivity
- 256 Gbps switching capacity for superior performance
- Advanced security features for network protection
- Energy-efficient design for reduced power consumption

Product Applications

- Small to medium-sized business networks requiring reliable and high-performance switches
- Connecting servers and storage devices in data centers
- Expanding networks in educational institutions for enhanced connectivity

Supported Options

Accessory	Model
External Power Supply	C9300-PSU
Rack Mount Kit	C9300-RACK-KIT
SFP+ Modules	C9300-SFP-10G

Compare to Similar Items

Model	Differences
Cisco C9200-24T	24x 10/100/1000 ports, no SFP+ ports
Cisco C9300-48T	48x 10/100/1000 ports, 4x 10 Gigabit SFP+ ports
Cisco C9500-24Q	24x 40 Gigabit QSFP+ ports

Get More Information

Do you have any questions about the C1300-24T-4X?

Contact us now via info@hi-network.com.



Specification

C1300-24T-4X Datasheet	
Ports	24x 10/100/1000 ports
Combo Ports	4x 10 Gigabit SFP+
Mounting	Rack-mountable
Forwarding Rate	95.23 Mpps
Switching Capacity	128.0 Gbps
Power	100-240V 50-60 Hz, internal, universal
Dimension	445 x 240 x 44 mm (17.5 x 9.45 x 1.73 in)
Weight	3.14 kg (6.92 lb)
Operating Temperature	23° to 122°F (-5° to 50°C)
Operating Humidity	10% to 90%, relative, noncondensing
Console port	Cisco standard RJ-45 console port and USB Type C port
USB port	USB Type C port on the front panel of the switch for easy file and image management as well as console port
Buttons	Reset button
Cabling type	Unshielded Twisted Pair (UTP) Category 5e or better for 1000BASE-T
LEDs	System, Link/Act, PoE, Speed
Flash	512 MB
CPU	ARM dual-core at 1.4 GHz
DRAM	1 GB DDR4
Certifications	UL (UL 62368), CSA (CSA 22.2), CE mark, FCC Part 15 (CFR 47) Class A

Want to Buy

Get a Quote

[Learn More](#) about Hi-Network[Search](#) our Resource Library[Follow](#) us on LinkedInContact for [Sales or Support](#)



Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: echo.hinetwork

WhatsApp Business: +8618057156223

