

Get a Quote

### Overview

C1941-SEC-SRE/K9 is the Cisco 1941 router with SRE Bundle, including SRE 300, and SEC license PAK.

### **Quick Specification**

Table 1 shows the Quick Specs of the C1941-SEC-SRE/K9.

Product Code	C1941-SEC-SRE/K9
Bundle	Cisco 1941 SRE Bundle, SRE 300, SEC Lic. PAK
Rack Units	2 RU
Interfaces	2 integrated 10/100/1000 Ethernet ports: GE0/0&GE0/1
Expansion Slot(s)	2 enhanced High-Speed WAN Interface Card slots 1 Internal Services Module slot
RAM	512 MB (installed) / 2 GB (max)
Flash Memory	256 MB (installed) / 8 GB (max)
Dimensions	34.3 cm x 29.2 cm x 8.9 cm

Figure 1 shows the front view of Cisco Router 1941. C1941-SEC-SRE/K9 is similar with it.







## **Bundle Features**

Figure 2 shows the Security License function.



#### Table 2 shows Cisco SRE Module Product Specifications. C1941-SEC-SRE/K9 supports SRE 300.

Feature	Cisco SRE 300 ISM	Cisco SRE 700 and SRE 710 SMs	Cisco SRE 900 and SRE 910 SMs
Product part	ISM-SRE-300-K9	SM-SRE-700-K9 SM-SRE-710-K9	SM-SRE-900-K9 SM-SRE-910-K9
number			
Form factor	ISM	SM	SM
CPU	Genuine Intel Processor, 1.06 GHz	Intel Core2 Solo, 1.86 GHz	Intel Core2 Duo, 1.86 GHz
DRAM	512 MB	4 GB	4 GB (default) or 8 GB
Compact Flash	4-GB internal USB flash-memory	2-GB internal USB flash-memory	2-GB internal USB flash-memory
memory	module	module	module
	None		Two 500-GB SATA
		One 500-GB SATA	(1 TB in non-RAID mode)
Hard disk		5400 rpm (SRE 700)	5400 rpm (SRE 900)
		7200 rpm (SRE 710)	7200 rpm (SRE 910)
Hot-swappable hard			
disk drive (HDD)	None	None	Yes
RAID support	None	None	RAID 0 or 1 (application dependent)
Internal network	Gigabit Ethernet connectivity to router	Gigabit Ethernet connectivity to router	Gigabit Ethernet connectivity to rout
interfaces	backplane	backplane	backplane
External network		One USB connector	One USB connector
interfaces	None	One RJ-45 Gigabit Ethernet connector	One RJ-45 Gigabit Ethernet connect
	Cisco 1941, 2901, 2911, 2921, 2951,	Cisco 2911, 2921, 2951, 3925, 3925E,	Cisco 2911, 2921, 2951, 3925, 3925
Router platforms	3925, and 3945 Integrated Services	3945, and 3945E Integrated Services	3945, and 3945E Integrated Services
	Routers	Routers	Routers



HI-NETWORK.com

our Global Oriainal Network Supplier



		1 -	
Cisco IOS Software (on router)	Release 15.0(1)M	Release 15.1(4)M	Release 15.1(4)M
Embedded hardware- based cryptography acceleration	No	No	Yes
Supported Application	s		
Supported Application	s • Cisco Unity Express • Cisco Application Extension Platform (AXP) • Cisco Wireless LAN Controller (WLC)	<ul> <li>Cisco Unity Express</li> <li>Cisco UCS Express</li> <li>Cisco AXP</li> <li>Cisco WLC</li> <li>Cisco Wide Area Application Services (WAAS)</li> <li>Infoblox Core Network Services</li> <li>Cisco Prime Network Analysis Module (NAM)</li> <li>Cisco Unified SIP Proxy</li> <li>Cisco Unified Messaging Gateway (UMG)</li> <li>Cisco Survivable Remote Site Voicemail (SRSV)</li> <li>Sagemcom Fax over IP</li> <li>Tiani Spirit Medical Data Exchange Solution</li> <li>Orion Health Rhapsody Connect</li> <li>NetScout nGenius Integrated Agent</li> <li>BlueCat Adonis DNS/DHCP and Proteus IPAM</li> <li>LogLogic MX-Virtual Appliance</li> <li>SecureLogix Voice Policy Firewall</li> <li>Open Text RightFax Fax over IP</li> <li>Visual Network Systems OmniPoint Element</li> <li>Uplogix Local Management Platform</li> <li>IndustryWeapon</li> </ul>	<ul> <li>Cisco Unity Express</li> <li>Cisco UCS Express</li> <li>Cisco AXP</li> <li>Cisco WLC</li> <li>Cisco Video Surveillance</li> <li>Infoblox Core Network Services</li> <li>Cisco Prime Network Analysis</li> <li>Module (NAM)</li> <li>Cisco Unified SIP Proxy</li> <li>Cisco Unified Messaging Gateway</li> <li>(UMG)</li> <li>Cisco Survivable Remote Site</li> <li>Voicemail (SRSV)</li> <li>Sagemcom Fax over IP</li> <li>Tiani Spirit Medical Data Exchange</li> <li>Solution</li> <li>Orion Health Rhapsody Connect</li> <li>NetScout nGenius Integrated Agent</li> <li>BlueCat Adonis DNS/DHCP and</li> <li>Proteus IPAM</li> <li>LogLogic MX-Virtual Appliance</li> <li>SecureLogix Voice Policy Firewall</li> <li>Open Text RightFax Fax over IP</li> <li>Visual Network Systems OmniPoint</li> <li>Element</li> <li>Uplogix Local Management Platform</li> </ul>
		• IndustryWeapon CommandCenterHD	• Industry Weapon CommandCenterHD

### **Compare to Similar Routers**

#### Table 3 shows the comparison between CISCO1941/K9 and C1941-SEC-SRE/K9.

Model	<u>CISCO1941/K9</u>	C1941-SEC-SRE/K9
Bundle	N/A	Cisco 1941 SRE Bundle, SRE 300, SEC license PAK
Rack Units	2 RU	2 RU





Interfaces	2 integrated 10/100/1000 Ethernet ports: GE0/0&GE0/1	2 integrated 10/100/1000 Ethernet ports: GE0/0&GE0/1
Expansion Slot(s)	2 enhanced High-Speed WAN Interface Card slots	2 enhanced High-Speed WAN Interface Card slots
	1 Internal Services Module slot	1 Internal Services Module slot
RAM	512 MB (installed) / 2.5 GB (max)	512 MB (installed) / 2.5 GB (max)
Flash Memory	256 MB (installed) / 8 GB (max)	256 MB (installed) / 8 GB (max)

### **Get More Information**

Do you have any question about the C1941-SEC-SRE/K9?

Contact us now via info@hi-network.com.

# Specification

C1941-SEC-SRE/K9 Specifications		
Manufacturer	Cisco Systems, Inc	
Manufacturer Part Number	C1941-SEC-SRE/K9	
Product Type	Cisco 1941, SRE 300, and SEC license PAK bundle	
Form Factor	Desktop - modular - 2U	
Connectivity Technology	Wired	
Data Link Protocol	Ethernet, Fast Ethernet, Gigabit Ethernet	
Network / Transport Protocol	IPsec, L2TPv3	
Routing Protocol	OSPF, IS-IS, BGP, EIGRP, DVMRP, PIM-SM, IGMPv3, GRE, PIM-SSM, static IPv4 routing, static IPv6 routing	
Remote Management Protocol	SNMP, RMON	
Features	Firewall protection, VPN support, MPLS support, Syslog support, IPv6 support, Class-Based Weighted Fair Queuing (CBWFQ), Weighted Random Early Detection (WRED)	
Compliant Standards	IEEE 802.3ah, IEEE 802.1ah, IEEE 802.1ag	
DRAM Memory	2 GB	
Flash Memory	256 MB (installed) / 8 GB (max)	
LED Status Lights Indicators	Link activity, power	
	Connectivity Slots	
	1 x 10Base-T/100Base-TX/1000Base-T - RJ-45	
	Management: 1 x console - RJ-45	
Router Interfaces	Management: 1 x console - mini-USB Type B	
	Serial: 1 x auxiliary - RJ-45	
	USB: 2 x 4 PIN USB Type A	
Expansion Slot(s)	2 (total) / 2 (free) x HWIC	



HI-NETWORK.com

our Global Original Network Supplier



	2 (total) / 1 (free) x CompactFlash Card		
	1 (total) / 1 (free) x Expansion Slot		
Power Supply			
Power Device	Power supply - internal		
Voltage Required	AC 120/230 V (50/60 Hz)		
	Dimensions / Weight / Miscellaneous		
Width	34.3 cm		
Depth	29.2 cm		
Height	8.9 cm		
Weight	5.8 kg		
Compliant Standards	CISPR 22 Class A, CISPR 24, EN55024, EN55022 Class A, EN50082-1, CAN/CSA-E60065-00, ICES-003 Class A, CS-03, AS/NZS 3548, FCC, FCC CFR47 Part 15, EN300-386, UL 60950-1, IEC 60950-1, EN 60950-1, CSA C22.2 No. 60065, BSMI CNS 13438		

### Want to Buy



# **Contact HI-NETWORK.COM For Global Fast Shipping**

HongKong Office Tel: +00852-66181601	
HangZhou Office Tel: +0086-571-86729517	
Email: info@hi-network.com	
Skype: echo.hinetwork	

WhatsApp Business: +8618057156223

