

[Get a Quote](#)

Overview

Cisco CBS220-48T-4X 48-Port Gigabit Managed Network Switch with SFP+

Quick Specification

| | |
|--------------------------|---|
| Product Code | CBS220-48T-4X |
| Inputs/Outputs | 48 x 10/100/1000 Mb/s Gigabit Ethernet (RJ45) PoE+ 4 x 10Gb SFP+ |
| Layer Services Supported | Layer 2 Support |
| Jumbo Frames Support | 9216 Bytes |
| MAC Address Table Size | 8K |
| VLAN Groups | 256 |
| Forwarding Rate | 130.94 Mpps |
| Switching Bandwidth | 176 Gb/s |
| AC Input Power | 110 to 220 VAC, 50 / 60 Hz |
| Dimensions | 17.3 x 10.1 x 1.7" / 440 x 257 x 44 mm |
| Weight | 7.8 lb / 3.54 kg |

Product Details:

The Front Panel:



The back panel



Get more information:

Do you have any question about the CBS220-48T-4X?

Contact us now via e-mail: info@hi-network.com

Specific Data Sheet:

| | |
|--------------------------|---|
| Interfaces | |
| Inputs/Outputs | 48 x 10/100/1000 Mb/s Gigabit Ethernet (RJ45) PoE+ 4 x 10Gb SFP+ |
| Protocols | |
| Layer Services Supported | Layer 2 Support |



| | |
|-----------------------------------|--|
| Supported Protocols | Auto-MDIX/MDI Head-of-Line (HOL) Blocking IGMP Snooping IPv4 IPv6 Link Aggregation MAC Filtering RADIUS |
| Queuing | Strict Priority, Weighted Round Robin (WRR) |
| Jumbo Frames Support | 9216 Bytes |
| MAC Address Table Size | 8K |
| VLAN Groups | 256 |
| Security | |
| Security Features | DoS Attack Prevention RADIUS Authentication |
| Access Control List | 512 |
| Standards | |
| Supported IEEE Standards | 802.1d, 802.1p, 802.1q, 802.1q/p, 802.1s, 802.1w, 802.1x, 802.3ad, 802.3af, 802.3at, 802.3az, 802.3u |
| Performance | |
| Forwarding Rate | 130.94 Mpps |
| Switching Bandwidth | 176 Gb/s |
| Packet Buffer | 16 Mb |
| Electrical | |
| Power Draw | 41.2 W (Max) |
| AC Input Power | 110 to 220 VAC, 50 / 60 Hz |
| Power Supply Type | Internal |
| Environmental | |
| Operating Temperature | 32 to 122°F / 0 to 50°C |
| Operating Humidity | 10 to 90% |
| Storage Temperature | -4 to 158°F / -20 to 70°C |
| Storage Humidity | 10 to 90% |
| Noise Level | 32.6 dB |
| General | |
| Cooling System | Fan |
| Mean Time Between Failures (MTBF) | 420,827 Hours |
| Dimensions | 17.3 x 10.1 x 1.7" / 440 x 257 x 44 mm |
| Weight | 7.8 lb / 3.54 kg |



Want to Buy?

Order Now

Get a Quote



Learn More about Hi-Network



Search our Resource Library



Follow us on LinkedIn



Contact for Sales or Support

Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: echo.hinetwork

