

[Get a Quote](#)

Overview

The Cisco 300 Series is broad portfolio of fixed-configuration managed Ethernet switches. Models are available with 8 to 48 ports of Fast Ethernet and 10 to 52 ports of Gigabit Ethernet connectivity, providing optimal flexibility to create exactly the right network foundation for your business. The Cisco SF302-08 provides 8 10/100 ports, 2 combo mini-GBIC ports.

Quick Specification

Product Code	SF302-08
Product Description	8 10/100 ports, 2 combo mini-GBIC ports
Ports	8 x 10/100 + 2 x combo Gigabit SFP
Power Over Ethernet (PoE)	N/A
Performance	Switching capacity : 5.6 Gbps Forwarding performance (64-byte packet size) : 4.17 Mpps
MAC Address Table Size	16K entries
Capacity	4K Active VLANs
Routing Protocol	Static IPv4 routing



Product Details:

The Front Panel:



Compare to Similar Items

Product Number	SF302-08	SF300-08
Product Description	8 10/100 ports, 2 combo mini-GBIC ports	8 10/100 ports
Ports	8 x 10/100 + 2 x combo Gigabit SFP	8 x 10/100
Power Over Ethernet (PoE)	N/A	N/A
Performance	Switching capacity : 5.6 Gbps Forwarding performance (64-byte packet size) : 4.17 Mpps	Switching capacity : 5.6 Gbps Forwarding performance (64-byte packet size) : 4.17 Mpps
MAC Address Table Size	16K entries	16K entries
Capacity	4K Active VLANs	4K Active VLANs
Routing Protocol	Static IPv4 routing	Static IPv4 routing

Get more information:

Do you have any question about the SF302-08?

Contact us now via e-mail: info@hi-network.com

Specific Data Sheet:

Product Number	SF302-08
Product Description	8 10/100 ports, 2 combo mini-GBIC ports

SF302-08 Datasheet



HI-NETWORK.com
Your Global Original Network Supplier

General	
Device Type	Switch - 8 ports - L3 - managed
Enclosure Type	Desktop, rack-mountable - 1U
Ports	8 x 10/100 + 2 x combo Gigabit SFP
Power Over Ethernet (PoE)	N/A
Performance	Switching capacity : 5.6 Gbps Forwarding performance (64-byte packet size) : 4.17 Mpps
MAC Address Table Size	16K entries
Capacity	4K Active VLANs
Routing Protocol	Static IPv4 routing
Remote Management Protocol	SNMP 1, RMON 1, RMON 2, RMON 3, RMON 9, Telnet, SNMP 3, SNMP 2c, HTTP, HTTPS, SSH, CLI
Jumbo Frame Support	10KB
Authentication Method	Secure Shell (SSH), RADIUS, TACACS+
Features	Layer 3 switching, layer 2 switching, DHCP support, BOOTP support, VLAN support, IGMP snooping, Syslog support, DoS attack prevention, port mirroring, DiffServ support, Weighted Round Robin (WRR) queuing, Broadcast Storm Control, IPv6 support, Multicast Storm Control, Unicast Storm Control, firmware upgradable, Spanning Tree Protocol (STP) support Rapid Spanning Tree Protocol (RSTP) support, Multiple Spanning Tree Protocol (MSTP) support, Trivial File Transfer Protocol (TFTP) support, Access Control List (ACL) support, Quality of Service (QoS), Jumbo Frames support, MLD snooping, fanless
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3z, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.1s
RAM	128 MB
Flash Memory	16 MB flash
Status Indicators	Link activity, port transmission speed, system
Expansion / Connectivity	
Interfaces	8 x 10Base-T/100Base-TX - RJ-45 1 x console - 9 pin D-Sub (DB-9) - management 2 x 10Base-T/100Base-TX/1000Base-T - RJ-45 2 x SFP (mini-GBIC)
Power	
Power Device	Internal power supply
Voltage Required	AC 120/230 V (50/60 Hz)
Miscellaneous	
Width	11 in
Depth	6.7 in
Height	1.5 in
Weight	2.6 lbs
Cables Included	1 x serial cable
Rack Mounting Kit	Included



MTBF	69,825 hour(s)
Compliant Standards	UL 60950, FCC Part 15 A, CSA 22.2
Localization	Chinese (simplified), English, German, French, Italian, Spanish, Japanese
Manufacturer Warranty	
Service Support	Limited lifetime warranty
Service Support Details	Limited warranty - replacement - lifetime - response time: next business day Technical support - web support - 1 year Technical support - phone consulting - 1 year
Environmental Parameters	
Min Operating Temperature	32 °F
Max Operating Temperature	104 °F
Humidity Range Operating	10 - 90% (non-condensing)
Min Storage Temperature	-4 °F
Max Storage Temperature	158 °F
Humidity Range Storage	10 - 90% (non-condensing)

Want to Buy?

Order Now

Get a Quote



Learn More about Hi-Network



Search our Resource Library



Follow us on LinkedIn



Contact for Sales or Support

Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: echo.hinetwork