

Get a Quote

Overview

SFP-10G-ER is the Cisco 10GBASE-ER Module supports a link length of up to 40 kilometers on standard Single-Mode Fiber (SMF, G.652).

Quick Specification

Cisco SFP+	SFP-10G-ER
Wavelength (nm)	1550
Cable Type	SMF
Core Size (Microns)	G.652
Modal Bandwidth (MHz*km)	-
Cable Distance	40km

Product Details:

The Front Panel:



Accessories For SFP-10G-ER:

Platform Support:

<p>7600 Series Router</p> <p>ASR 901</p> <p>ASR-903</p> <p>ASR 1000 Series Router</p> <p>ASR 9000 Series Router</p> <p>ASR 9000v Series Router</p> <p>Catalyst 2350 and 2360 Series Switches</p> <p>Catalyst 2960-S, 2960-X, and 2960-XR Series Switches</p> <p>Catalyst 3100 Blade Switches</p> <p>Catalyst 3560, 3560-E, and 3560-X Series Switches</p> <p>Catalyst 3750, 3750-E, and 3750-X Series Switches</p> <p>Catalyst 3850 Series Switches</p>	<p>Catalyst 4500 and 4500-X Series Switches</p> <p>CRS Router</p> <p>MDS 9000</p> <p>ME 4500</p> <p>ME 4900NCS 6000 Series Router</p> <p>Nexus 2000, 3000, and 4000 Series Switches</p> <p>Nexus 9000 and 9500 (modular) Series Switches</p> <p>RF Gateway Series</p> <p>SCE 8000</p> <p>Shared Port Adapter (SPA)</p> <p>Unified Computing System (UCS) Switches</p>
---	---

Compare to Similar Items:

Cisco SFP+	Wavelength (nm)	Cable Type	Core Size (Microns)	Modal Bandwidth (MHz*km)	Cable Distance
<p>Cisco SFP-10G-SR-Sa</p> <p>Cisco SFP-10G-SR</p> <p>Cisco SFP-10G-SR-X</p>	850	MMF	62.5	160 (FDDI)	26m
			62.5	200 (OM1)	33m
			50.0	400	66m
			50.0	500 (OM2)	82m
			50.0	2000 (OM3)	300m
			50.0	4700 (OM4)	400m
Cisco SFP-10G-LRM	1310	MMF	62.5	500	220m
		SMF	50.0	400	100m
			50.0	500	220m
			G.652	-	300m
<p>Cisco SFP-10G-LR-Sa</p> <p>Cisco SFP-10G-LR</p> <p>Cisco SFP-10G-LR-X</p>	1310	SMF	G.652	-	10km
<p>Cisco SFP-10G-ER-S</p> <p>Cisco SFP-10G-ER</p>	1550	SMF	G.652	-	40km

Get more information:

Do you have any question about the SFP-10G-ER?

Contact us now via e-mail: info@hi-network.com

Specific Data Sheet:

Transmit and Receive Wavelength (nm)	1530 to 1565
Cable Type	10GBASE-ER 1550nm SMF
Core Size (Microns)	G.652
Modal Bandwidth (MHz*km)	-
Cable Distance	40km
Transmit Power (dBm)	Maximum: 4.0 Minimum: -4.7
Receive Power (dBm)	Maximum: -1 Minimum: -15.8
Bail Latch Color	Red
Power Consumption (W)	1.5
Operating Temperature Range	COM

Want to Buy

Get a Quote



[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)

Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: echo.hinetwork

WhatsApp Business: +8618057156223

