

## Overview

The EchoLife EG8120L is an intelligent routing-type ONT that provides one GE port, one POTS port, and one FE port. The EG8120L features high-performance service forwarding capabilities to ensure excellent experiences with VoIP, Internet, and HD video services. Therefore, the EG8120L provides a perfect terminal solution and future-oriented service-supporting capabilities for networks.

## Quick Specification

Table 1 shows the Quick Specification.

Model	EchoLife EG8120L
Dimensions (H x W x D)	30 mm x 94 mm x 115 mm (without external antenna and pads)
Weight	Approximately 155 g
Operating Temperature	0°C to +40°C
Operating Humidity	5% RH to 95% RH (non-condensing)
Power Adapter Input	100V to 240V AC, 50/60 Hz
System Power Supply	11V to 14V DC, 1A
Static Power Consumption	3.8 W
Maximum Power Consumption	4.9 W
NNI	GPON
UNI	1GE + 1FE + 1POTS
Optical Connector	SC/APC

Figure 1 shows the appearance of EchoLife EG8120L.



## Product Details

### Interface Parameters

GPON Port	<ul style="list-style-type: none"> <li>• Class B+</li> <li>• Receiver sensitivity: -27dBm ~ -29dBm</li> <li>• Overload optical power: -8 dBm</li> <li>• Wavelengths: US 1310 nm, DS 1490 nm</li> <li>• Wavelength blocking filter (WBF)</li> <li>• Flexible mapping between GEM Port and TCONT</li> <li>• GPON: consistent with the SN or password authentication defined in G.984.3</li> <li>• Bi-directional FEC</li> <li>• SR-DBA and NSR-DBA</li> <li>• Type B (single-homing &amp; dual-homing)</li> </ul>
Ethernet Port	<ul style="list-style-type: none"> <li>• Ethernet port-based VLAN tags and tag removal</li> <li>• 1:1 VLAN, N:1 VLAN, or VLAN transparent transmission</li> <li>• QinQ VLAN</li> <li>• Limit on the number of learned MAC addresses</li> <li>• MAC address learning</li> <li>• Local switching/isolation based on Ethernet ports</li> <li>• Transparent transmission of IPv6 packets at Layer 2</li> </ul>
POTS Port	<ul style="list-style-type: none"> <li>• Maximum REN: 4</li> <li>• G.711A/μ, G.729a/b, and G.722 encoding/decoding</li> <li>• T.30/T.38/G.711 fax mode</li> <li>• DTMF</li> <li>• Emergency calls (with the SIP protocol)</li> </ul>

### Product Function

Smart Interconnection	<ul style="list-style-type: none"> <li>• SIP/H.248 auto-negotiation</li> <li>• Any port any service</li> <li>• Parental control</li> </ul>
Smart O&M	<ul style="list-style-type: none"> <li>• Variable-length OMCI messages</li> <li>• Active/Passive rogue ONT detection and isolation</li> <li>• PPPoE/DHCP simulation testing</li> <li>• Call emulation, and circuit test and loop-line test</li> <li>• eSight management</li> </ul>
Multicast	<ul style="list-style-type: none"> <li>• IGMP v2/v3 snooping</li> <li>• MLD v1/v2 snooping</li> <li>• Fast leave</li> <li>• VLAN tag translation, transparent transmission, and removal for downstream multicast packets</li> </ul>



	<ul style="list-style-type: none"> <li>• IGMP/MLD protocol packet rate limitation</li> </ul>
QoS	<ul style="list-style-type: none"> <li>• Ethernet port rate limitation</li> <li>• 802.1p priority</li> <li>• SP/WRR/SP+WRR</li> <li>• Broadcast packet rate limitation</li> <li>• Flow mapping based on the VLAN ID, port ID, or/and 802.1p</li> </ul>
Security	<ul style="list-style-type: none"> <li>• MAC address filtering</li> </ul>
Common O&M	<ul style="list-style-type: none"> <li>• OMCI/Web UI</li> <li>• Dual-system software backup and rollback</li> <li>• 802.1ag Ethernet OAM</li> <li>• Optical link measurement and diagnosis</li> <li>• Loopback check</li> </ul>
Power Saving	<ul style="list-style-type: none"> <li>• Indicator power saving</li> <li>• Power consumption reduction of idle components in power-saving state</li> <li>• COC V5</li> </ul>

## Get More Information

Do you have any question about the EchoLife EG8120L?

Contact us now via [info@hi-network.com](mailto:info@hi-network.com).

## Specification

EchoLife EG8120L Specification	
Dimensions (H x W x D)	30 mm x 94 mm x 115 mm (without external antenna and pads)
Weight	Approximately 155 g
Operating Temperature	0°C to +40°C
Operating Humidity	5% RH to 95% RH (non-condensing)
Power Adapter Input	100V to 240V AC, 50/60 Hz
System Power Supply	11V to 14V DC, 1A
Static Power Consumption	3.8 W
Maximum Power Consumption	4.9 W
NNI	GPON
UNI	1GE + 1FE + 1POTS
Optical Connector	SC/APC
Indicators	POWER/PON/LOS/LAN/TEL



Get a Quote



<p>GPON Port</p>	<ul style="list-style-type: none"> <li>• Class B+</li> <li>• Receiver sensitivity: -27dBm ~ -29dBm</li> <li>• Overload optical power: -8 dBm</li> <li>• Wavelengths: US 1310 nm, DS 1490 nm</li> <li>• Wavelength blocking filter (WBF)</li> <li>• Flexible mapping between GEM Port and TCONT</li> <li>• GPON: consistent with the SN or password authentication defined in G.984.3</li> <li>• Bi-directional FEC</li> <li>• SR-DBA and NSR-DBA</li> <li>• Type B (single-homing &amp; dual-homing)</li> </ul>
<p>Ethernet Port</p>	<ul style="list-style-type: none"> <li>• Ethernet port-based VLAN tags and tag removal</li> <li>• 1:1 VLAN, N:1 VLAN, or VLAN transparent transmission</li> <li>• QinQ VLAN</li> <li>• Limit on the number of learned MAC addresses</li> <li>• MAC address learning</li> <li>• Local switching/isolation based on Ethernet ports</li> <li>• Transparent transmission of IPv6 packets at Layer 2</li> </ul>
<p>POTS Port</p>	<ul style="list-style-type: none"> <li>• Maximum REN: 4</li> <li>• G.711A/μ, G.729a/b, and G.722 encoding/decoding</li> <li>• T.30/T.38/G.711 fax mode</li> <li>• DTMF</li> <li>• Emergency calls (with the SIP protocol)</li> </ul>

## Want to Buy

Get a Quote



[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)

## Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: [info@hi-network.com](mailto:info@hi-network.com)

Skype: echo.hinetwork

WhatsApp Business: +8618057156223

