

## Overview

The Huawei EchoLife EG8245H is a routing-type ONT in the Huawei all-optical access solution. It uses the GPON technology to implement ultra-broadband access for users.

It provides 4 GE+2 POTS+1 USB+1 Wi-Fi (4 GE ports, 2 POTS ports, 1 USB port, and 1 2.4G WiFi port). The high forwarding performance ensures the user experience of voice, data, and HD video services, and provides customers with an ideal all-optical access solution and future-oriented service support capability.

## Quick Specification

Table 1 shows the Quick Specification.

Model	EchoLife EG8245H
Dimensions (H x W x D)	176 mm x 138.5 mm x 28 mm (without an external antenna)
Weight	About 280 g
Operating temperature	0°C to +40°C
Operating humidity	5% RH to 95% RH (non-condensing)
Power adapter input	100 – 240 V AC, 50/60 Hz
System power supply	11 – 14 V DC, 1.5 A
Static power consumption	5.5 W
Maximum power consumption	16.5 W
Ports	2POTS + 4GE + Wi-Fi+ 1USB
Indicators	POWER/PON/LOS/LAN/TEL/USB/WLAN/WPS

Figure 1 shows the appearance of EchoLife EG8245H.



## Product Details

### Interface Parameters

GPON Port	<ul style="list-style-type: none"> <li>● Class B+</li> <li>● Receiver sensitivity: -27 dBm</li> <li>● Wavelengths: US 1310 nm, DS 1490 nm</li> <li>● WBF</li> <li>● Flexible mapping between GEM Port and TCONT</li> <li>● GPON: consistent with the SN or password authentication defined in G.984.3</li> <li>● Bi-directional FEC</li> <li>● SR-DBA and NSR-DBA</li> </ul>
Ethernet Port	<ul style="list-style-type: none"> <li>● Ethernet port-based VLAN tags and tag removal</li> <li>● 1:1 VLAN, N:1 VLAN, or VLAN transparent transmission</li> <li>● QinQ VLAN</li> <li>● Limit on the number of learned MAC addresses</li> <li>● MAC address learning</li> </ul>
POTS Port	<ul style="list-style-type: none"> <li>● Maximum REN: 4</li> <li>● G.711A/μ, G.729a/b and G.722 encoding/decoding</li> <li>● T.30/T.38/G.711 fax mode</li> <li>● DTMF</li> <li>● Emergency calls (with the SIP protocol)</li> </ul>
USB Port	<ul style="list-style-type: none"> <li>● USB2.0</li> <li>● FTP-based network storage</li> </ul>
WLAN	<ul style="list-style-type: none"> <li>● IEEE 802.11 b/g/n</li> <li>● 2 x 2 MIMO</li> <li>● Antenna gain: 5 dBi</li> <li>● WMM</li> <li>● Multiple SSIDs</li> <li>● WPS</li> <li>● Air interface rate: 300 Mbit/s (2.4G)</li> </ul>

### Product Function

Smart Interconnection	<ul style="list-style-type: none"> <li>● Smart Wi-Fi coverage</li> <li>● SIP/H.248 auto-negotiation</li> <li>● Any port any service</li> <li>● Parental control</li> <li>● L2/L3 (IPv4) forwarding: 1G uplink, 2G downlink</li> </ul>
Smart Service	<ul style="list-style-type: none"> <li>● Smart Wi-Fi sharing: <ul style="list-style-type: none"> <li>– Portal/802.1x authentication</li> </ul> </li> </ul>



	<ul style="list-style-type: none"> <li>– SoftGRE-based sharing</li> <li>• Association of one account with two POTS ports</li> </ul>
Smart O&M	<ul style="list-style-type: none"> <li>• IPTV video quality diagnosis</li> <li>• Variable-length OMCI messages</li> <li>• Active/Passive rogue ONT detection and isolation</li> <li>• Call emulation, and circuit test and loop-line test</li> <li>• PPPoE/DHCP simulation testing</li> <li>• WLAN emulation</li> </ul>
Layer 3 Features	<ul style="list-style-type: none"> <li>• PPPoE/Static IP/DHCP</li> <li>• NAT/NAPT</li> <li>• Port forwarding</li> <li>• ALG, UPnP</li> <li>• DDNS/DNS server/DNS client</li> <li>• IPv6/IPv4 dual stack, and DS-Lite</li> <li>• Static/Default routes</li> <li>• Multiple services on one WAN port</li> </ul>
Multicast	<ul style="list-style-type: none"> <li>• IGMP v2/v3 proxy /snooping</li> <li>• MLD v1/v2 snooping</li> </ul>
QoS	<ul style="list-style-type: none"> <li>• Ethernet port rate limitation</li> <li>• 802.1p priority</li> <li>• SP/WRR/SP+WRR</li> <li>• Broadcast packet rate limitation</li> </ul>
Security	<ul style="list-style-type: none"> <li>• SPI firewall</li> <li>• Filtering based on MAC/IP/URL addresses</li> </ul>
Common O&M	<ul style="list-style-type: none"> <li>• OMCI/Web UI/TR069</li> <li>• Dual-system software backup and rollback</li> </ul>
Power Saving	<ul style="list-style-type: none"> <li>• Indicator power saving</li> <li>• Scheduled Wi-Fi shutdown</li> </ul>

## Get More Information

Do you have any question about the EchoLife EG8245H?

Contact us now via [info@hi-network.com](mailto:info@hi-network.com).

## Specification

EchoLife EG8245H Specification	
Dimensions (H x W x D)	176 mm x 138.5 mm x 28 mm (without an external antenna)
Weight	About 280 g
Operating temperature	0°C to +40°C





Operating humidity	5% RH to 95% RH (non-condensing)
Power adapter input	100 – 240 V AC, 50/60 Hz
System power supply	11 – 14 V DC, 1.5 A
Static power consumption	5.5 W
Maximum power consumption	16.5 W
Ports	2POTS + 4GE + Wi-Fi+ 1USB
Indicators	POWER/PON/LOS/LAN/TEL/USB/WLAN/WPS
GPON Port	<ul style="list-style-type: none"> <li>● Class B+</li> <li>● Receiver sensitivity: -27 dBm</li> <li>● Wavelengths: US 1310 nm, DS 1490 nm</li> <li>● WBF</li> <li>● Flexible mapping between GEM Port and TCONT</li> <li>● GPON: consistent with the SN or password authentication defined in G.984.3</li> <li>● Bi-directional FEC</li> <li>● SR-DBA and NSR-DBA</li> </ul>
Ethernet Port	<ul style="list-style-type: none"> <li>● Ethernet port-based VLAN tags and tag removal</li> <li>● 1:1 VLAN, N:1 VLAN, or VLAN transparent transmission</li> <li>● QinQ VLAN</li> <li>● Limit on the number of learned MAC addresses</li> <li>● MAC address learning</li> </ul>
POTS Port	<ul style="list-style-type: none"> <li>● Maximum REN: 4</li> <li>● G.711A/μ, G.729a/b and G.722 encoding/decoding</li> <li>● T.30/T.38/G.711 fax mode</li> <li>● DTMF</li> <li>● Emergency calls (with the SIP protocol)</li> </ul>
USB Port	<ul style="list-style-type: none"> <li>● USB2.0</li> <li>● FTP-based network storage</li> </ul>
WLAN	<ul style="list-style-type: none"> <li>● IEEE 802.11 b/g/n</li> <li>● 2 x 2 MIMO</li> <li>● Antenna gain: 5 dBi</li> <li>● WMM</li> <li>● Multiple SSIDs</li> <li>● WPS</li> <li>● Air interface rate: 300 Mbit/s (2.4G)</li> </ul>

## Want to Buy

[Get a Quote](#)




[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)

## Contact HI-NETWORK.COM For Global Fast Shipping

---

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: [info@hi-network.com](mailto:info@hi-network.com)

Skype: [echo.hinetwork](https://www.skype.com/people/echo.hinetwork)

WhatsApp Business: +8618057156223

