

Overview


The OptiXstar P813E is an ONU designed for scenarios such as enterprise campus and video backhaul. It provides 8 GE ports with PoE/PoE+ to provide high-quality voice, data, and HD video services.

Quick Specification

Table 1 shows the Quick Specification.

Model	OptiXstar P813E
Dimensions (W x D x H)	220mm x 150mm x 35mm (Without floor mat)
Weight	About 1030g
Operating Temperature	-5°C to 45°C
Operating Humidity	5% to 95% RH (non-condensing)
Power Adapter Input	100-240 V AC, 50/60 Hz
System Power Supply	56 V DC, 2.6A
NNI	XGS-PON
UNI	8*GE (PoE/PoE+)
Static Power Consumption	8 W
Maximum PoE Output Power	Gross power 120W (up to 30W for one GE port)

Figure 1 shows the appearance of OptiXstar P813E.





Product Details

Port Parameters

SFP	<ul style="list-style-type: none"> ● XGS-PON optical module, port type: SC/UPC ● XGS-PON; <ul style="list-style-type: none"> – Class N1/N2; – Receiver sensitivity: -28dBm; – Overload optical power: -9dBm; – Transmission rate: upstream 9.953 Gbit/s, downstream 9.953 Gbit/s ● Type B single-homing ● Type B dual-homing (supported in Layer 2 forwarding)
GE	<ul style="list-style-type: none"> ● PoE and PoE+, complying with IEEE 802.3af and IEEE 802.3at ● Port type: RJ-45 ● Auto ports speed (10/100/1000 Mbit/s) ● Auto-MDI/MDIX ● Configuration of the number of MAC addresses learned ● VLAN transparent transmission/VLAN filtering

Product Function

Automatic Service Provisionin	<ul style="list-style-type: none"> ● Authenticati on exemption ● XML/OMCI/TR069
Smart O&M	<ul style="list-style-type: none"> ● XML/Web UI ● Rogue ONT detection and self-regulation ● Ring network detection/PPPoE/DHCP simulation testing
Layer 3 Features	<ul style="list-style-type: none"> ● Default/Static/Policy/Service routes ● VLAN binding ● ALG/UPnP/ARP ● DDNS/DMZ/DNS/NAPT ● PPPoE/Static IP/DHCP ● Port mapping/Port trigger ● IPv6
Layer 2 Management	<ul style="list-style-type: none"> ● DHCP Option82 ● PITP ● BPDU transparent transmission ● LLDP/LLDP-MED
Multicast	<ul style="list-style-type: none"> ● IGMP v2/v3 snooping ● Dynamic controllable multicast ● IGMP proxy ● MLDv1/MLDv2 snooping





QoS	<ul style="list-style-type: none"> • Ethernet port rate limitation • 802.1p priority • SP/WRR/SP+WRR
Security	<ul style="list-style-type: none"> • 802.1x • IPv6/IPv4 firewalls • Filtering based on MAC/IP/URL • DoS/ARP anti-attacks • Static MAC address binding • Device access control • Web session number restriction

Compare to Similar Items

Table 2 shows the comparison.

Model	OptiXstar P802E	OptiXstar P803E	OptiXstar P812E	OptiXstar P813E
NNI	XGS-PON	XGS-PON	XGS-PON	XGS-PON
UNI	4*GE	8*GE	4*GE+1*2.5GE NOTE: Both the GE and 2.5GE ports support PoE/PoE+	8*GE (PoE/PoE+)

Get More Information

Do you have any question about the OptiXstar P813E?

Contact us now via info@hi-network.com.

Specification

OptiXstar P813E Specification	
Dimensions (W x D x H)	220mm x 150mm x 35mm (Without floor mat)
Weight	About 1030g
Operating Temperature	-5°C to 45°C
Operating Humidity	5% to 95% RH (non-condensing)
Power Adapter Input	100-240 V AC, 50/60 Hz
System Power Supply	56 V DC, 2.6A
NNI	XGS-PON
UNI	8*GE (PoE/PoE+)





Static Power Consumption	8 W
Maximum Power Consumption	12 W (POE port without PD) 143 W (POE port with PD having the maximum power consumption)
Maximum PoE Output Power	Gross power 120W (up to 30W for one GE port)
Surge Protection Specifications	GE: common mode 4 kV; differential mode 0.5 kV. AC power: common mode 6 kV; differential mode 6 kV.
SFP	<ul style="list-style-type: none"> • XGS-PON optical module, port type: SC/UPC • XGS-PON; <ul style="list-style-type: none"> – Class N1/N2; – Receiver sensitivity: -28dBm; – Overload optical power: -9dBm; – Transmission rate: upstream 9.953 Gbit/s, downstream 9.953 Gbit/s • Type B single-homing • Type B dual-homing (supported in Layer 2 forwarding)
GE	<ul style="list-style-type: none"> • PoE and PoE+, complying with IEEE 802.3af and IEEE 802.3at • Port type: RJ-45 • Auto ports speed (10/100/1000 Mbit/s) • Auto-MDI/MDIX • Configuration of the number of MAC addresses learned • VLAN transparent transmission/VLAN filtering
Installation Mode	Support indoor desktop installation, wall mounting, or network box installation.

Want to Buy

[Get a Quote](#)

[Learn More](#) about Hi-Network

[Search](#) our Resource Library

[Follow](#) us on LinkedIn

 Contact for [Sales or Support](#)

Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: [echo.hinetwork](https://www.skype.com/addtocontactlist/echo.hinetwork)

WhatsApp Business: +8618057156223

