

[Get a Quote](#)

Overview

Huawei SFP-10G-USR is Optical Transceiver. It's a Multi-mode Module.

Quick Specification

Table 1 shows the Quick Specs.

Model	SFP-10G-USR
Part Number	02310MNW
Transceiver form factor	SFP+
Transmission speed	10 Gbit/s
Center wavelength (nm)	850
Standard compliance	10Gbase-USR
Connector type	LC
Applicable cable and maximum transmission distance	Multimode fiber (OM3): 0.1km
Transmit power (dBm)	-7.3 to -1.0
Maximum receiver sensitivity (dBm)	-10.7
Overload power (dBm)	0.5
Extinction ratio (dB)	3.0
Operating temperature	0°C to 70°C (32°F to 158°F)
Net Dimension (D x W x H mm)	145 x 80 x 35

The Supported Switches

Figure 1. SFP-10G-USR can be installed in the switch's SFP slot.



Table 2 shows the Huawei hot switches which support SFP-10G-USR.

Model	Description
S5700-28P-LI-AC	24 x Ethernet 10/100/1000 ports, 4 Gig SFP, AC 110/220V
S5700-28TP-LI-AC	24 x Ethernet 10/100/1000ports,2 Gig SFP and 2 dual-purpose 10/100/1000 or SFP, AC 110/220V
S5700S-52P-LI-AC	48 x Ethernet 10/100/1000 ports, 4 Gig SFP, AC 110/220V

SFP-10G-USR (02310MNW)

Datasheet



HI-NETWORK.com
Your Global Original Network Supplier

S5700-28P-PWR-LI-AC	24 x Ethernet 10/100/1000 PoE+ ports, 4 Gig SFP, AC 110/220V
S5700-10P-PWR-LI-AC	8 x Ethernet 10/100/1000 PoE+ ports, 2 Gig SFP, AC 110/220V
S5720-36C-EI-AC	28 x Ethernet 10/100/1000 ports, 4 of which are dual-purpose 10/100/1000 or SFP, 4 10 Gig SFP+, 1 interface slot, with 150W AC
S5700-28C-EI-AC	24 x Ethernet 10/100/1000 ports, with 1 interface slot, with 150W AC power supply
S5720-56C-HI-AC	48 x Ethernet 10/100/1000 ports, 4 10 Gig SFP+, with 2 interface slots, with 600W AC power supply
S5720-56PC-EI-AC	48 x Ethernet 10/100/1000 ports, 4 Gig SFP, with 1 interface slot, with 150W AC power supply
S5720-56C-PWR-HI-AC	48 x Ethernet 10/100/1000 POE+ ports, 4 10 Gig SFP+, with 2 interface slots, with 1150W AC power supply

Compare to Similar Items

Table 3 shows the comparison of SFP-10G-USR and OSX010000.

Item	SFP-10G-USR	OSX010000
Transceiver form factor	SFP+	SFP+
Transmission speed	10 Gbit/s	10 Gbit/s
Center wavelength (nm)	850	1310
Standard compliance	10Gbase-USR	10Gbase-LR
Connector type	LC	LC
Applicable cable and maximum transmission distance	Multimode fiber (OM3): 0.1 km	Single-mode fiber: 10 km
Transmit power (dBm)	-7.3 to -1.0	-8.2 to +0.5
Maximum receiver sensitivity (dBm)	-10.7	-12.6
Overload power (dBm)	0.5	0.5
Extinction ratio (dB)	3	3.5
Operating temperature	0°C to 70°C (32°F to 158°F)	0°C to 70°C (32°F to 158°F)
Net Dimension (D x W x H mm)	145 x 80 x 35	110 x 70 x 37

Get more information:

Do you have any question about the SFP-10G-USR (02310MNW) ?

Contact us now via email: info@hi-network.com

Specification:

Transceiver form factor	SFP+
Transmission speed	10 Gbit/s
Center wavelength (nm)	850
Standard compliance	10Gbase-USR
Connector type	LC
Applicable cable and maximum transmission distance	Multimode fiber (OM3): 0.1km
Transmit power (dBm)	-7.3 to -1.0
Maximum receiver sensitivity (dBm)	-10.7



SFP-10G-USR (02310MNW) Datasheet



HI-NETWORK.com
Your Global Original Network Supplier

Overload power (dBm)	0.5
Extinction ratio (dB)	3.0
Operating temperature	0°C to 70°C (32°F to 158°F)
Net Dimension (D x W x H mm)	145 x 80 x 35

Want to Buy

Get a Quote



[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales](#) or [Support](#)

Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: echo.hinetwork

WhatsApp Business: +8618057156223

